



FLATKOTE

For use on plastered walls, woodwork, metal ceilings, wall-boards and all interior surfaces where oil or water paints are generally used.

"United" Flatkote is a leadless, non-poisonous oil paint which dries with the soft matt appearance of the highest grade distemper, and embodies the washable and non-fading qualities of a good oil paint.

"United" Flatkote spreads as freely as a thin oil paint, and flows out like varnish without showing brush marks or laps, enabling a large area to be covered with the utmost ease.

"United" Flatkote is sanitary, germ-proof and washable, and is therefore a most suitable coating for interior walls of private residences, hospitals, offices, theatres, churches, public halls, etc., where the utmost cleanliness and durability are essentials.

"United" Flatkote is unsurpassed for use in interior decoration of the home, and the beautiful shades available allow the user to give effect to his own colour schemes with the most harmonious results. Its appeal to the Home Decorator is further enhanced by its restful reaction to light—instead of light being reflected with a glare it is diffused with a gentle brilliancy.

"United" Flatkote is made in 24 colours, Black and White, but an almost endless variety of intermediate tones may be produced by intermixing the various colours and reducing with White for very pale tints.

Manufactured by
AUSTRALASIAN UNITED PAINT CO. LTD.
Melbourne, Sydney, Adelaide.



FLATKOTE

DIRECTIONS FOR USE.

"UNITED FLATKOTE" is supplied in heavy consistency to permit of suitable reduction for various coats, and to meet the needs of special surface conditions.

PRIMING COAT Use two parts "United" Priming Oil to one part "United Flatkote," with a little turpentine if found necessary.

FIRST COAT: Use half each "United" Priming Oil and "United Flatkote," with a little Turpentine if necessary.

SECOND COAT: It is advisable to allow the first coat to harden well before applying the final coat, allowing at least 24 hours. Then apply "United Flatkote" thinned with approximately $\frac{1}{2}$ gallon Turpentine to one gallon "United Flatkote." It is essential that "United Flatkote" be flowed on with a long haired soft brush and not brushed out as ordinary paint.

IMPORTANT.

It is necessary that all cracks and holes in wall be stopped with plaster and allowed to thoroughly harden for twenty-four hours before applying the Priming Coat. Care should be taken to well incorporate the whole contents of the tin. The following method will be found most effective:—

First: Pour off as much of the liquid as possible.

Next: Thoroughly stir the balance until it becomes a smooth creamy mass, then gradually replace liquid previously removed.

Finally: Pour the paint from the original container into a clean tin and back again, repeating the operation three times.

Manufactured by
AUSTRALASIAN UNITED PAINT CO. LTD.
Melbourne, Sydney, Adelaide.



Products For the Home

"United" Pure Prepared Paint.

A ready-mixed paint of the highest quality, ready for application on exterior and interior surfaces where maximum protection and durability, combined with proper decorative effects, are desired. "United" is an Australian-made Paint, prepared, ground and mixed under rigid supervision, and will stand up to any durability test.

"United" Cement Paving Paint.

Gives life and brightness to cement verandahs and footpath. Is made from highest quality pigments and ground in specially prepared mediums of water-resisting properties.

"United" Oil Varnish Stain.

A popular range of Stains, specially recommended for use on interior surfaces, such as floors, doors, frames, woodwork, fixtures and furniture.

"United" Household Enamel.

Another popular line with an attractive range of colours. The Enamel covers solidly in one coat and dries quickly with a hard glossy surface.

"United" Silvasheen.

The well-known silvery finish. For baths, heaters, coppers, pipes, stoves and all iron surfaces about the house.

No matter what you want to paint, there is a "United" Product for that purpose, which will prove the best you can use.

Our advice is always available to the property owner who may care to submit for consideration any problems in decoration.

Printed at Frearson's, Hindmarsh, S.A.



FLATKOTE

A flat Oil Paint





FLATKOTE Producing the Artistic Effect of Water Colours, with the Durability of Oil Paint



TAN COLOUR



MAROON



SILVER GREY YELLOW STONE PALE BLUE CREAM STONE
FRIEZE COLOUR IVORY



IVORY



SEA GREEN



CORAL PINK PINK MAUVE BLUE ADAM GREEN
FRIEZE COLOUR LEMON TINT



PINK

BUFF
FRIEZE COLOUR

DRAB
CREAM STONE

BISCUIT



PEACH BLOW



LEMON TINT



SAGE GREEN

WARM STONE
FRIEZE COLOUR

DEEP GREEN
LIGHT STONE

OYSTER



LIGHT STONE



DARK BROWN.

